

# ADHERO Floor Drain

Floor drain as part of the SOLITEX ADHERO system



## Technical data

		Substance
Material		PVC
Attribute	Regulation	Value
Colour		grey
Thickness		3.5 mm ; 1/8"
Height		320 mm ; 12 5/8"
Outer diameter		Flange: 300 mm ; 11 13/16"
Outer diameter		Pipe: 63 mm ; 2 1/2"

## Application

Fitting for vertical drainage through the ceiling or roof structure during the construction phase. Installation with connection to a pipe or tube system for temporary drainage of water.

## Advantages

- ✓ Quick installation: simply drill through the building component, no cutting necessary
- ✓ Dependable drainage: reliable run-off thanks to extra-flat flange, low fitting height
- ✓ Watertight bonding: transition between SOLITEX ADHERO and floor drain can be sealed with TESCON VANA adhesive tape with SOLID adhesive
- ✓ Time-saving and reliable drainage: connection to pipes and tubes for temporary drainage



The information provided here is based on practical experience and the current state of knowledge. We reserve the right to make changes to the recommended designs and processing or to make alterations due to technical developments and associated improvements in the quality of our products. We would be happy to inform you of the current technical state of the art at the time you use our products.

Further information about the application and construction can be found in the pro clima planning documentation. For queries please call the pro clima technical hotline on +49 (0)6202 278245.

**MOLL**  
**bauökologische Produkte GmbH**  
Rheintalstraße 35 - 43  
D-68723 Schwetzingen  
Fon: +49 (0) 62 02 - 27 82.0  
eMail: info@proclima.de

